

# MONORAIL

## MONORAIL CURVE

### DESCRIPTION

Monorail is rated for 300 watts at 12 volts and 600 watts at 24 volts. Each piece of rail is shipped with straight conductive connectors to join rail pieces end to end. Order additional connectors (p. 461) if cutting and rejoining rails. All pieces are field-cutttable and hand-bendable to a horizontal radius as small as 6 inches.




BRONZE



SATIN NICKEL

### 24" DIAMETER CIRCLE

1/3 Round, Radius 12". Order three pieces to create a 24" diameter circle.




MODEL	RAILCV3-	
FINISH	BZ62.5-2 bronze	SC62.5-2 satin nickel

sample item number **RAILCV3-BZ62.5-2** 24" diameter circle, bronze

### 48" DIAMETER CIRCLE

1/3 Round, Radius 24". Order three pieces to create a 48" diameter circle.




MODEL	RAILCV2-	
FINISH	BZ125-2 bronze	SC125-2 satin nickel

sample item number **RAILCV2-SC125-2** 48" diameter circle, satin nickel

### SOFT CURVE

78" Diameter, 1/5 Round, Radius 39". Order five pieces to create a 78" diameter circle.



MODEL	RAILCV1-	
FINISH	BZ117-2 bronze	SC117-2 satin nickel

sample item number **RAILCV1-SC117-2** soft curve, satin nickel

FIXTURE TYPE _____
JOB NAME _____
NOTES _____
_____
_____



7400 Linder Ave.  
Skokie, Illinois 60077

T 847.626.6300  
F 847.626.6350

[lblighting.com](http://lblighting.com)



© 2014 LBL Lighting. All rights reserved. The "LBL Lighting" graphic is a registered trademark of LBL Lighting. LBL Lighting reserves the right to change specifications for product improvements without notification.